

LOW PRESSURE, HIGH VOLUME

HIGH-FLO[®] Pumps**Model SWO-B00169, Series A: KING 3:1, HF, CS, Bare***270 psi (18 bar) MAXIMUM FLUID WORKING PRESSURE**90 psi (6.3 bar) MAXIMUM AIR INPUT PRESSURE***Model 6880280, Series A: Viscount II, 300 HF, SST, Bare***300 psi (21 bar) MAXIMUM FLUID WORKING PRESSURE**1500 psi (103 bar) MAXIMUM HYDRAULIC FLUID PRESSURE*

These products are similar to products described in Manual 307 678. This sheet makes this manual also valid for the products above. Please note the deviations below and keep this sheet with your manual.

Parts

Model No.	Similar Product	Part of Deviation	Ref. No.	Part Description	Description of deviation
SWO-B00169	218-528	220-106	101	QUIET KING AIR MOTOR.	Standard King Air Motor p/n 207-647 is used. See 306-968 for parts.
6880280	218-538	218-531	102	DISPLACEMENT PUMP.	DISPLACEMENT PUMP, BSP p/n 240-467 is used. See page 37 for parts.

Technical Data

Sound Pressure Level King Air Motor..... 98 dBa

Sound Power Level King Air Motor..... 113 dBa

