

Viscount II Pump

800 psi (56 bar) MAXIMUM HYDRAULIC FLUID INTAKE PRESSURE

400 psi (28 bar) MAXIMUM FLUID WORKING PRESSURE

Model 098 090, Series A

Viscount I+ Pump, BSP

1500 psi (103 bar) MAXIMUM HYDRAULIC FLUID INTAKE PRESSURE

450 psi (31 bar) MAXIMUM FLUID WORKING PRESSURE

Model 6880286, Series A

These products are similar to products described in Manual 307 809. This sheet makes this manual also valid for the products above. Please note the deviations below and keep this sheet with your manual.

Parts

Model No.	Similar Product	Part of Deviation	Ref. No.	Part Description	Description of deviation
098 090	220-577	215-255	101	AIR MOTOR	Viscount II p/n 223-646 is used. <i>See 307-678 for parts.</i>
		183-033	102	TIE ROD	183-348 is used.
		108-284	104	O-RING	158-674 is used.
		183-041	105	COUPLING	183-084 is used.
		220-551	107	LOWER PUMP	220-557 is used. <i>See separate parts list on page 30.</i>
		108-527	108	NUT	108-683 is used.
		181-096	113	PLATE DESIGNATION	172-816 is used.
		183-343	-	ADAPTER PLATE	Added with SCREWS p/n 108-764 and WASHERS 100-128.
6880286	236-602	220-553	107	DISPLACEMENT PUMP	DISPLACEMENT PUMP, BSP p/n 240-613 is used. <i>See 308-793 for parts.</i>

