

WALL MOUNT AIR - ASSISTED PACKAGES



Bare Unit , without Spray gun 6880276	<i>210 bar(3000 psi) MAXIMUM FLUID WORKING PRESSURE 7 bar (100 psi) MAXIMUM AIR INLET PRESSURE</i>
--	--

This product is similar to the products described in Manual 308-756. This sheet makes this manual also valid for the products above. Please note the deviations below and keep this sheet with your manual.

Parts

Model No.	Similar Product	Part of Deviation	Ref. No.	Part Description	Description of deviation
6880276	232-201	214-961	30	Suction hose	Suction hose p/n 214-960 is used
		156-591	31	Elbow 90°	Part is not used.
		156-593	32	o-ring	Part is not used.
		156-592	33	Suction tube	Suction tube p/n 192-121 is used.
		176-684	34	Adapter	Part is not used.
		100-220	35	Thumbscrew	Part is not used.
		159-101	36	Housing	Strainer p/n 181-073 is used.
		161-377	37	Filter screen	Part is not used.
		159-100	38	Stop	Part is not used.

⚠ WARNING

- The installed air relief valve is required for safe operation of the pump. To reduce the risk of serious injury from moving parts, fluid injection, or splashing when shutting off the pump, two accessories, a bleed-type master air valve and a fluid drain valve are required for your system
- If your system is not properly grounded, sparking may occur and the system may become hazardous.